

Steel fireplace KRATKI FLOKI M left 10 kW Ø 200

SKU: FLOKI/M/L EAN: 5903751242338



Technical data

General data

Version	Corner left
Nominal power (kW)	10
Heating power range (kW)	7-13
Thermal Efficiency (%)	83.6
Flue gas temperature (oC)	235
Max billet length (cm)	50
Minimum required active area of inlet grilles (cm2)	500
Minimum required active field of outlet grilles (cm2)	700
diameter of the flue gas outlet	200
Color	Black
CLOSING	No
Base material	Steel
Door opening	Left

Energetic efficiency

Energy class	A+
EEl	111
Seasonal Energy Efficiency (%)	74
Heat output for space heating (kW)	10
CO emission (at 13% O2) ≤ given in %	0.082
CO emission (mg/m3)	1033
Pollen emission (mg/m3)	28
NOx emission (mg/m3)	135
OGC emission (mg/m3)	74
Flue gas mass flow (g/s)	9

Certifications / Compliance

Certificates	Ecodesign, Designed for recuperation, BImSchV 2
--------------	--

Additional information

Equipment	Air intake - built in , Ashpan, Combustion chamber lining, Decorative glass
FRONT	Steel front with painted glass
Fuel type	Seasoned deciduous wood (humidity $\leq$20%)
EAN	5903751242338

Physical parameters

Width (cm)	79.9
Height (cm)	120.4
Depth (cm)	49.4
Weight (kg)	154.54

