



KRATKI INGA

The Kratki Inga is part of Kratki's premium freestanding fireplace range, crafted to be a true statement piece that brings luxurious design and cutting-edge heating technology to your space. This large fireplace has a commanding scale that creates a striking feature and focal point in the room. Its expansive 3 sided glass door, framed with a sleek blackened edge design, creates a bold and modern aesthetic. The refined handle with a click-shut mechanism adds to the high-end feel.

Its rectangular steel body and large glass windows offer a striking view of the flames, while advanced combustion technology ensures efficient heating and low emissions. Powerful and high-performing, this wood-burning fireplace is ideal for contemporary spaces that value both style and comfort.

This Kratki closed combustion fireplace is built for lasting strength and performance. Its robust steel construction, combined with Kratki's signature thick ceramic internals, ensures exceptional durability and heating performance - a fireplace engineered to deliver reliable warmth for generations.

Categories: [All fireplaces](#), [Freestanding wood fireplaces](#), [Wood fireplaces](#)

Tags: [Closed-combustion](#), [Heat intensifying ceramics](#), [Modern](#)

PRODUCT GALLERY



ADDITIONAL INFORMATION

Weight	203 kg
Dimensions	53.8 × 46.8 × 146.6 cm
CO emissions	0.07%
Colour	Black
Country of manufacture	Poland
Efficiency	80%
Flue pipe diameter	150mm
Fuel	Wood
Heat output	8 – 11 kW
Heating capacity	160 – 275m ³
Material	Steel
Warranty	10-year warranty
Ash pan	Yes
Combustion technology	Primary, secondary and tertiary combustion
Door	Standard door
Fan system	No
Flue exit	Top or rear
Label	New

PRODUCT DESCRIPTION

Inside the fireplace chamber, Kratki's signature ceramic lining enhances both combustion efficiency and long-term durability. These heat-intensifying ceramics deliver exceptional thermal performance, supporting primary and secondary combustion for a cleaner burn and maximum heat output. By maintaining consistently high temperatures within the combustion chamber, the ceramics make the fireplace easier to operate, improve heat delivery, and significantly reduce soot buildup in the flue system. Lining the chamber with ceramics provides the highest level of protection to the steel structure, extending the lifespan of the fireplace.

The fireplace features primary, secondary, and tertiary combustion, all controlled through a single air control lever for simple operation.

A double deflector system enhances combustion efficiency and heat retention, ensuring optimal warmth with reduced fuel use.

The body of the fireplace is built from high-quality, thick steel, ensuring exceptional resistance to high temperatures. Each unit is precision-welded in a shielded noble gas environment for superior structural integrity and airtight performance. Using advanced laser-cutting and CNC bending technology, every steel component is crafted with accuracy and consistency to guarantee a perfect fit and long-lasting durability.

Special attention has been given to the top section of the fireplace, which is crafted from 5 mm thick steel to ensure exceptional strength and resistance to high temperatures.

A large glass door panels frame the flames beautifully, while Kratki's superior heat-resistant glass and air-wash system help keep the viewing window clear. For improved safety and performance, as well as to increase their lifespan, the heat-resistant glass that Kratki uses is of the highest quality.

Kratki's signature fireplace grate design is engineered using thick cast iron, featuring re-enforced ribbing and multiple bends to maximise strength, durability, and long-term performance.

The removable ash box allows for simple and easy cleaning.

The comfortable handle features a solid, ergonomic design with a modern aesthetic. The smooth door closing mechanism holds the door in place with a click latch shut.

Depending on your preferred aesthetic and installation, this freestanding fireplace allows for both top or rear flue exit.

Direct fresh air system can be installed where only outside air supplies the fire - built-in external air inlet is 125mm diameter.

A set of adjustable feet allow for the fireplace to be easily set level and at an exact height.

Built to deliver lasting warmth and reliability, all Kratki wood-burning fireplaces are backed by a 10-year warranty, reflecting Kratki's commitment to quality, performance, and longevity.

NOTES



Kratki South Africa

www.kratki.co.za | info@kratki.co.za
